

# HISTORIC™ ANTIQUE POLYURETHANE FINISHES

Commercial and Residential Polyurethane Coating for Hardwood Floors

**PROFESSIONAL USE ONLY. KEEP AWAY FROM AND OUT OF REACH OF CHILDREN.**

**CAUTION: COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL SOURCES OF IGNITION.**

Extinguish all pilot lights; disable all water heaters, furnaces, etc. Use with adequate ventilation; do not allow vapors to accumulate and concentrate in areas such as basements, bathrooms or small-enclosed areas. Open all windows and doors to ensure cross ventilation across work area. Use properly maintained and fitted NIOSH approved respirator for organic solvent vapors. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye watering, STOP and get fresh air immediately.

**PRECAUTIONS:** This product should only be applied by professionals knowledgeable in safe and proper use. Do not use steel wool for screening if using a waterborne finish. Do not thin. Do not apply in extremely cold or humid weather.

**DANGER! CONTAINS PETROLEUM DISTILLATES.** Harmful or fatal if swallowed. Reports have associated prolonged repeated overexposure to solvents with neurological and other physiological damage. Refer to MSDS for more information.

**DISPOSAL:** Rags, steel wool and other waste soaked with oil finishes may spontaneously catch fire if improperly discarded. Dispose of rags and waste products in a sealed metal container or in accordance with local government and fire regulations.

**DO NOT TAKE INTERNALLY.** Avoid prolonged or repeated breathing of vapors or spray mist. Avoid contact with eyes or prolonged contact with skin. Close container after each use and do not reuse this container.

**FIRST AID:** If swallowed, do not induce vomiting. Call poison control center, hospital emergency room or physician immediately. In case of eye contact, immediately flush with water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. For more information about this product, its application, or safety procedures, contact the manufacturer and/or consult MSDS.

**STORAGE:** Store at room temperature. Do not store above 120°F. Protect from freezing. If frozen, thaw at room temperature without stirring, and then stir before using. Keep container in upright position and tightly closed when storing.

**V.O.C. content:** Antique FLAT = 520 g/l Antique Matte = 523 g/l Antique Satin = 520 g/l Antique Semi-Gloss = 515 g/l

NON-PHOTOCHEMICALLY REACTIVE – UN #1263



## New Installations or Refinishing:

1. Sand floors according to NWFA procedures. Any existing finish on floor must be removed to ensure proper adhesion. Sweep, vacuum, and then tack bare wood with virgin mineral spirits and allow to dry 30 minutes.
2. Stir contents well before use. Turn off all fans and HVAC systems during application. Apply with roller, lambs wool applicator, brush, or T-bar style applicator @ 500 sq ft/gal.
3. Allow airflow when floor is tack free (usually 4 – 5 hrs). Allow overnight dry before application of next coat and abrade between coats with new 150 grit screen or used 120 grit.
4. Keep traffic off floor for 48 hours. Light traffic until 7 days, normal traffic after that. Historic Floor and the NWFA recommend no rugs for 30 days. Coating will reach 80% cure in 7 days, full cure in 30 days.

## Screen and Recoats:

1. Tack floor first with Tie Tack® prior to screening.
2. Screen floor with 120 used screen.
3. Sweep, vacuum, and then tack with water (no mineral spirits). Allow to thoroughly dry.
4. Apply finish.

## GUARANTEE

*We guarantee this Historic™ Floor product to perform as advertised when applied in accordance with industry standards. Because surface preparation, application methods, and environmental conditions are beyond our control, all expressed and implied warranties are explicitly excluded. Responsibility for claim of any kind is limited to product purchase price or product replacement only.*